

Zed Zed's Workbench

Amateur Radio Projects & More!

🔧 A Simple 2 m/70 cm Vertical Dipole Antenna

This easy to build dual band VHF/UHF antenna makes a great project for the new ham that is ready to get on the 2 meter and 70 centimeter amateur radio bands. It can be mounted on a roof top for use as a fixed antenna and it also folds conveniently for travel making it an excellent backpack antenna. The design is simple and so is construction.

Download PDF

Printable PDF (Free)

Download Here


frompdfdoc.com

OPEN

🔧 Construction

The antenna elements are made of 1/8" diameter stainless steel rod. Each rod is bent into a tight "U" shape and fastened to the acrylic plexiglass boom with stainless steel hardware. Flat washers large enough to fit across the gap in each element are used to hold the elements in place. A piece of 1/4" thick cast acrylic plexiglass, 18" long and 2-1/2" wide, is used for the boom.

Drill the holes in the boom as shown in the diagram. The position and hole size for the mast mounting clamp is determined by the size and width of the clamp or U-bolt that you use. I used a TV antenna mast clamp that fits a 1-1/4" mast.



Probably the hardest part in making this antenna is bending the stainless steel rod. But the rod can be bent without heating it first with a torch. I was able to bend the rod by placing it in a bench vise. The tricky part is to bend two pieces of rod that come out looking similar in shape. Use two pieces of stainless steel rod that are longer than needed then trim them to correct lengths after the rod has been folded into a U shape. Make each element section as shown in the next diagram.

🔧 Video Instructions


Watch the video below to learn how to build this antenna.

Ham Radio 2m/70cm Vertical Dipole Ante...




👍 Like Share 318 people like this. Sign Up to see what your friends like.

I used mostly all #6 stainless steel hardware to attach the antenna elements to the boom. Start by placing an external tooth lock washer on a machine screw then insert it into the hole drilled in the boom. Next install a flat washer, then the antenna element, then another flat washer. The ring connectors with the coaxial cable attached go on next then finally fasten with a split lock washer and a wing nut. Repeat for the opposite side.



🔧 Tuning the Antenna

To tune the antenna for minimum SWR simply loosen the wing nuts and slide the antenna elements in or out as needed. Keep in mind that changes made to one band will affect the other band. For example if you shorten the 2 meter length then you also shorten the 70 cm length. Some fine tuning by again trimming either the 2 meter or 70 cm sections may be done if desired but this should not be needed.



The hardware for mounting the antenna elements to the boom is also used to connect the feed line to the antenna. The coaxial cable center and shield are separated and the leads kept as short as possible. Crimp-on ring connectors, with the plastic insulation removed, are soldered to the ends of the cable. The coaxial cable center lead is connected to the top section and the shield is connected to the bottom section of the antenna. This antenna was fed with RG-8X (Mini 8) 50 ohm coaxial cable. The feed line used was a random length and was not cut to any specific length.



Parts List

All stainless steel element mounting hardware. Use larger size hardware if flat washers do not extend across both sides of the antenna element.

- 2 each 1/8" Stainless steel rod, 3' (.9 m) long.
- Acrylic Plexiglass, 18" x 2-1/2" x 1/4" (45.7 cm x 6.4 cm x 7 mm).
- 2 each #6 x 32 x 1" (25 mm) Machine screws.
- 2 each #6 x 32 Wing nuts.
- 4 each #6 Large flat washers.
- 2 each #6 Split lock washers.
- 2 each #6 External tooth lock washers.
- 2 each #6 Crimp-on ring connectors.
- Mast mount clamp.
- Plastic cable tie or small U-bolt.

Printable PDF (Free)



Safety First!

Please use caution and keep common sense safety rules in mind when installing an antenna. Never install antennas near power lines or in any location that would place people or pets within the near field radiation pattern of an antenna. All users understand and agree that the owner of this web site is not responsible for accidents or other mishaps that may have been caused directly or indirectly as a result of the information published on this web site and/or in any of the video presentations.

[Home](#) | [Antenna Projects](#) | [Other Projects](#) | [Clip Art](#) | [Links](#)

Copyright © 2011 KG0ZZ. All rights reserved.